

SMART NETWORK INTERFACE

A low-cost, vehicle diagnostics & flashing tool



DG-SNI is a low-cost CAN and Keyword interface tool designed to communicate to vehicle diagnostic networks. The SNI includes a J2534 API for reprogramming and pass-through diagnostics. This tool can be used for flashing the ECU on CAN and KWP2000.

Compact Size

The DG-SNI has a compact size which increases its portability. Weighing approximately 2.8 oz makes this tool easy to use on the road.

Key Features

Diagnostic and Flashing on CAN & KWP2000.

J2534 API for reprogramming and pass-through diagnostics

Wide Input Voltage Range (7.5-32V)

Vehicle Battery Read (VBAT) support

Compact size

Low-cost

USB 1.1 PC Connection

Allows PC to be isolated from vehicle

OBDII to DB9 J1962

Cable 12V

Product Specifications

TECHNICAL SPECIFICATIONS:

Enclosure Size: 0.88"X4.25" X 2.60" Color: Black																				
Weight 2.8 oz																				
Input Voltage 7.5V-32V																				
Current Consumption Vehicle Supply 200mA (max), PC Interface 100mA (max)																				
Operational Temperature range: Up to 85° C (informal test), Component rated: -40 ° C to 85 ° C)																				
Humidity 20% to 85% R.H.																				
Shock endurance 1.5 Meter Drop																				
Pin assignment <table><tr><td>Vehicle side: DB-9 Male</td><td>PC side: DB-9 Male</td></tr><tr><td>Pin1 K-LINE</td><td>Pin1 N/C</td></tr><tr><td>Pin2 CAN_L</td><td>Pin5 Ground</td></tr><tr><td>Pin3 NC</td><td>Pin6 USB Power</td></tr><tr><td>Pin4 NC</td><td>Pin8 USB D+</td></tr><tr><td>Pin5 Ground</td><td>Pin9 USB D-</td></tr><tr><td>Pin6 L-Line</td><td></td></tr><tr><td>Pin7 CAN_H</td><td></td></tr><tr><td>Pin Unswitched Vehicle Battery</td><td></td></tr><tr><td>Pin9 (-0/5V input switch)</td><td></td></tr></table>	Vehicle side: DB-9 Male	PC side: DB-9 Male	Pin1 K-LINE	Pin1 N/C	Pin2 CAN_L	Pin5 Ground	Pin3 NC	Pin6 USB Power	Pin4 NC	Pin8 USB D+	Pin5 Ground	Pin9 USB D-	Pin6 L-Line		Pin7 CAN_H		Pin Unswitched Vehicle Battery		Pin9 (-0/5V input switch)	
Vehicle side: DB-9 Male	PC side: DB-9 Male																			
Pin1 K-LINE	Pin1 N/C																			
Pin2 CAN_L	Pin5 Ground																			
Pin3 NC	Pin6 USB Power																			
Pin4 NC	Pin8 USB D+																			
Pin5 Ground	Pin9 USB D-																			
Pin6 L-Line																				
Pin7 CAN_H																				
Pin Unswitched Vehicle Battery																				
Pin9 (-0/5V input switch)																				
PC Connection USB Ver 1.1																				
Vehicle Connection CAN/ISO 15765 ISO9141/ISO14230																				