

VSI-2534 Quickstart Guide



1



4



2

2



2

3

Instructions:

- 1 Install J2534-compliant PC drivers from the VSI-2534 CD.
The latest J2534-compliant PC Drivers can always be found at <http://www.dgtech.com>.
- 2 Using the USB cable, connect the VSI-2534 to your PC. Connect the vehicle cable to the VSI-2534.
- 3 Finally, connect the other end of the vehicle cable to the vehicle's diagnostic port.
- 4 Configure your J2534-compliant OEM application to use the VSI-2534. Consult either the documents available from the OEM or review the applicable VSI-2534 Reprogramming User Guide located on the CD. The VSI-2534 User Guide and Reprogramming User Guides are also available in: Start > Programs > VSI-2534.

VSI-2534 Accessories



DG-VSI-2534-CABLE
6' OBDII TO DB-25 Male Cable



DG-15-1-USB-CABLE
15' USB CABLE



DG-OBDDII-BOX
16 PIN BREAKOUT BOX



DG-HD-BOB
9/15/25-PIN BREAKOUT BOX



DG-EXT-Warranty
1 Year Extended Warranty



DG-EXT2-Warranty
2 Year Extended Warranty



PE-20301
Palmer ScanXL STD



PE-20302
Palmer ScanXL PRO




RA-SST-PC
RA CONSULTING SST



PE-20310
Palmer ScanXL GM ENH
GM Enhanced Add-On



PE-20311
Palmer ScanXL FORD ENH
FORD Enhanced Add-On



PE-20312
Palmer ScanXL MAZDA ENH
MAZDA Enhanced Add-On